



The "Africa" 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.

## F40JMHDL



TECHNICAL CHARACTERISTICS	F40JMHDL
<b>MOTOR</b>	
Engine Type	In-line 4
Ignition System	Electronic Ignition (TCI)
Reduction ratio	9.4 :1
Start-up	Electric with Prime Start™
Power system	3 carburetors
Lubrication system	Unleaded
Fuel consumption (L/h-tr/min)	15.2 L/h @5500 r/min
Fuel	Wet Sump
Full throttle operating range (tr/min)	5000-6000
Max.Prop Shaft Horsepower (Kw)	29.4 (40 hp)
Bore x Stroke (mm)	65.0 X 75.0
Architecture	L3
Displacement (cc)	747
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	14 A
Control	Remote Control
<b>DIMENSIONS</b>	
Dry weight with propeller (kg)	95
Engine transom height (mm)	L: 536 (21.1 inch)
Oil capacity (L)	1.7 L / 1.5 L
<b>EQUIPMENTS</b>	
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
Kill Switch	✓
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	11 3/8



Always wear a helmet, eye protection and protective proper clothing.  
YAMAHANIGERIA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

